

# Concept PLUS Series

Economical metering pump solutions!



ProMinent®

The **ProMinent® Concept Plus** series covers a capacity range of **0.18 to 3.93 GPH (0.7 to 14.9 L/h)** at pressures up to **232 psi (16 bar)**.

*Its compact construction and features make it ideal for use in flow proportional or on/off control applications. The Concept Plus mounts easily onto a tank or wall bracket. Adjustment of the pump capacity is via the stroke length in the range of 10-100 % or can be set at 1 of the 4 stroke frequency settings. This gives an adjustment ratio of 40:1.*

## Features & Benefits

- NSF 61 approved
- Low cost opens up opportunities in the most basic applications
- PVDF wetted ends eliminate compatibility concerns
- Integral bleed valve prevents “loss of prime”
- Lowest maintenance costs in its class
- External control via dry contact pulse (1:1)
- Wetted end materials: PP, Acrylic/PVC or PVDF

## Applications

- Swimming pools
- Spas, fountains and spray pads
- Cooling towers
- Boiler feed applications
- General Chlorination
- Municipal and industrial wastewater
- Water disinfection
- Biocide feed
- “Pump on a drum” applications

# Concept PLUS Series

## Technical data

Capacity Data											
Pump Version	Capacity at Maximum Back Pressure				mL/stroke	Max. Stroking Rate	Pre-Primed Suction Lift		Tubing Connectors O.D. x I.D.	Shipping Weight (approx.)	
	psig	(bar)	GPH	(L/h)			ft.	(m)		(in.)	lbs.
<b>CNPb</b>											
1000	145	(10)	0.18	(0.7)	0.07	180	20	(6)	1/4 x 3/16	3.97	(1.8)
1601	232	(16)	0.29	(1.1)	0.10	180	20	(6)	1/4 x 3/16	3.97	(1.8)
1002	145	(10)	0.55	(2.1)	0.19	180	16	(5)	1/4 x 3/16	3.97	(1.8)
1003	145	(10)	0.79	(3.0)	0.21	240	16	(5)	1/4 x 3/16	3.97	(1.8)
0704	102	(7)	1.03	(3.9)	0.41	180	13	(4)	1/4 x 3/16	3.97	(1.8)
0705	102	(7)	1.37	(5.2)	0.36	240	13	(4)	1/4 x 3/16	3.97	(1.8)
0309	43.5	(3)	2.40	(9.0)	0.83	180	20	(6)	3/8 x 1/4	3.97	(1.8)
0215	29	(2)	3.93	(14.9)	1.45	180	5	(1.5)	3/8 x 1/4	3.97	(1.8)

External pulse contact retrofit available as an option (P/N 1022000)

## Identity code pump configuration

CNPb	Concept PLUS										
Version	Capacity					Version	Capacity				
1000	0.18 gph (0.7 l/h), 145 psi (10 bar)					0704	1.03 gph (3.9 l/h), 102 psi (7 bar)				
1601	0.29 gph (1.1 l/h), 232 psi (16 bar)					0705	1.37 gph (5.2 l/h), 102 psi (7 bar)				
1002	0.55 gph (2.1 l/h), 145 psi (10 bar)					0309	2.40 gph (9.0 l/h), 43.5 psi (3 bar)				
1003	0.79 gph (3.0 l/h), 145 psi (10 bar)					0215	3.93 gph (14.9 l/h), 29 psi (2 bar)				
<b>Liquid end material:</b>											
PP Polypropylene											
NP Acrylic/PVC											
PV PVDF											
<b>O-rings:</b>											
B Viton® seals											
E EPDM seals											
T PTFE seals											
<b>Liquid end version:</b>											
0 Non-bleed version, no valve spring											
1 Non-bleed version, with valve spring											
2 With bleed valve, no valve spring (except 0704 models)											
3 With bleed valve, with valve spring											
<b>Connection:</b>											
M 1/4" x 3/16"											
N 3/8" x 1/4"											
<b>Logo:</b>											
0 With ProMinent® logo											
<b>Power Supply:</b>											
A 1 ph 230 V 50/60 Hz (Euro plug)											
D 1 ph 115 V 50/60 Hz (US plug)											
4 1 ph 230 V 50/60 Hz (US plug) (consult factory for pricing)											
<b>Control Option:</b>											
0 Standard (w/o external control)											
B With external and level input retrofit kit, fitted, without level switch											
<b>Accessories:</b>											
1 With accessories (foot valve, injection valve, tubing)											
<b>Control Variant:</b>											
0 Standard											
<b>Approval:</b>											
01 CE											
07 MET											
11 MET + NSF 61											
CNPb	1000	PP	B	0	M	0	A	0	1	0	01